

# Consilex Floor

Protective coating, glossy or matt, for stamped concrete floors



Consilex Floor is a water-based acrylic resin for the protection of concrete, decorative cement-based surfaces, stamped floors or washed gravel floors. It is particularly suitable for outdoor use. Consilex Floor has excellent penetration into the cementitious material, it is not yellowing, it has good resistance to abrasion, water, atmospheric agents and UV rays.

**CUSTOMS CODE:** 3824 9970

**COMPONENTS:** Single-component

**APPEARANCE:** Liquid

**AVAILABLE COLORS:** Transparent / Neutral

**PACKAGING AND DIMENSIONS:** Plastic can 25 l

## ALLOWED SUPPORTS

Concrete - Natural stones


## APPLICATION METHODS


Low pressure airless nebulizer


## TOOL CLEANING


Water


## KEY FEATURES

 Density: 0.91 kg/dm<sup>3</sup>

 Solvent-based product

 UV-resistant

 Shelf-life: 12 months

 Temperature of use: +5 / +35 °C

## TECHNICAL SPECIFICATIONS

Dust-free time at 20°C **2 - 3 h**

Deep hardening at 20°C **24 h**



## CONSUMPTION

From 0.12 to 0.15 liters of Consilex Floor per coat for each square meter of surface to be treated, based on the porosity of the substrate.

## STORAGE AND CONSERVATION

Protect from freezing. Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance. Protect from humidity.

## PHOTO GALLERY



## WARNINGS AND PRECAUTIONS

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge. Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage. Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: [www.azichem.com](http://www.azichem.com). The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: [www.azichem.com](http://www.azichem.com).

It is forbidden to dispose of the product and/or packaging in the environment.

