

Sealpvc SF 250 Bulb

Waterstop in PVC for dynamic construction joints resting on the bottom



The Sealpvc SF 250 Bulb waterstop is a waterproofing PVC profile that is not hydro-expansive, having a thickness of 25 centimetres and equipped with a central and highly elastic bulb. It is used in dynamic joints for horizontal casting (slabs), in concrete structures, resting on the substrate beneath the reinforcement, in a position central to the casting.

CUSTOMS CODE: 3925 9010

COMPONENTS: Single-component

APPEARANCE: Extruded PVC

AVAILABLE COLORS: Black / Light blu

PACKAGING AND DIMENSIONS: Roll 25 m

FEATURES AND BENEFITS

PVC waterstops are highly elastic waterproof profiles that are used in concrete structures, positioning them as recovery and expansion joints, thus ensuring perfect hydraulic sealing and the ability to absorb mechanical and natural stresses.

Specifically, the SEALPVC SF 250 BULB profile is made of high-quality thermoplastic vinyl resins with the addition of a particular and specific plasticizer.

The profile has excellent performance characteristics and is highly resistant to:

- the aggressive action of acid-alkaline solutions,
 - aging,
 - brackish water
 - degradation caused by the sun, ozone and other atmospheric or chemical agents normally present in the air and groundwater.
- The flexibility of SEALPVC SF 250 BULB is high even at low temperatures and its mechanical characteristics remain unchanged over time. Given its particular composition, it can be cut with a sharp blade (cutter) and welded with simple heat welding tools, thus making it easy to create connections during construction.

FIELDS OF APPLICATION

Waterproofing of dynamic construction joints between: raft foundation and the elevation wall, between two raft foundations, between two elevation walls, between the wall and floor, resting on foundations under the shoring.

ALLOWED SUPPORTS

Concrete

MODE OF USE

Bind with iron wire the side flaps of the waterstop to the steel plates provided, in order to position it and secure it in a central position with respect to the casting to be made. Proceed with the casting operations, ensuring it does not bend nor move from the seat identified.

APPLICATION METHODS

Apply by hand

KEY FEATURES



Nonflammable



UV-resistant



Unlimited shelf-life



Width: 250 mm

TECHNICAL SPECIFICATIONS

ISO 527

Longitudinal elongation at break **$300 \pm 3 \%$**

UL94

Flash-point **Classe V-O**

ISO 868

Hardness **75 ± 3 Shore A**

ISO 1183

1.38 ± 0.02 g/cm³

ISO 458/2

Cold Flex Temperature **-30 °C**

ISO 527

Breaking load longitudinal **12 ± 2 N/mm²**

Working temperature **$-30 / +70$ °C**



CONSUMPTION

1 m/m: Use Sealpvc SF 250 Bulb welding the two edges of different belts head to head using a leister (manual hot air welder).

STORAGE AND CONSERVATION

Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight.

PHOTO GALLERY



Produced and distributed by **AZICHEM srl**
Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy
Tel: +39 0376.604185 / 604365
Fax: +39 0376 604398
www.azichem.com - info@azichem.com

Update of **06-12-2024**
Terms of sale and legal notices available at
<https://www.azichem.com/general-sales-conditions>
Total pages of this document: 3

ADDITIONAL CONTENT



WARNINGS AND PRECAUTIONS

Pay careful attention both to the positioning of the waterstop and to any welds. Incorrect positioning could indeed nullify the performance. The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge. Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage. Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: www.azichem.com. The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: www.azichem.com.

It is forbidden to dispose of the product and/or packaging in the environment.

