

## Sealpvc SF 320



**CUSTOMS CODE:** 3925 9010  
**COMPONENTS:** Single-component  
**APPEARANCE:** Extruded PVC  
**AVAILABLE COLORS:** Black / Light blu  
**PACKAGING AND DIMENSIONS:** Roll 20 m - Roll 25 m

### ALLOWED SUPPORTS


Concrete

### APPLICATION METHODS

Apply by hand

### KEY FEATURES

 Nonflammable

 UV-resistant

 Unlimited shelf-life

 Width: 320 mm

### TECHNICAL SPECIFICATIONS

*ISO 527*  
Longitudinal elongation at break **300 ± 3 %**

*UL94*  
Flash-point **Classe V-0 %**

*ISO 868*  
Hardness **75 ± 3 Shore A**

*ISO 1183*  
**1.38 ± 0.02 g/cm<sup>3</sup>**

*ISO 458/2*  
Cold Flex Temperature **-30 °C**

*ISO 527*  
Breaking load longitudinal **12 ± 2 N/mm<sup>2</sup>**

Working temperature **-30 / +70 °C**



## STORAGE AND CONSERVATION

Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight.

## PHOTO GALLERY



| Dimensioni (mm) |          |        |         |
|-----------------|----------|--------|---------|
| SEALPVC SF 320  | A = 3,05 | D = 19 | L = 320 |

## WARNINGS AND PRECAUTIONS

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge. Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage. Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: [www.azichem.com](http://www.azichem.com). The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: [www.azichem.com](http://www.azichem.com).

It is forbidden to dispose of the product and/or packaging in the environment.

